SPARKMAN S TEPHENS DESIGN NO. 0097-c2 A NEW LOOK AT BABE

PRINCIPAL CHARACTERISTICS

Length Overall	30'-6''
Length at DWL	27'-6"
Beam, Maximum	8'-3''
Draft, Maximum	5'-6"
Displacement, Light	5,640 lbs
Ballast	2,400 lbs
Sail Area	460 ft ²
Fuel Oil	12 gallons
Fresh Water	13 gallons
Holding Tank	6 gallons

CONSTRUCTION

FRP/foam core sandwich hull & deck

E-glass and vinylester/polyester resin with cross-linked PVC structural foam core

Solid FRP laminate on centerline

Lightweight FRP/foam core bulkheads & interior Solid FRP laminate keel sump, engine pan, and hull structural grid

External lead keel mounted to molded keel sump Core removed or substituted with high density in way of deck hardware and thru-hull fittings

PROPULSION

Yanmar 2YM15xSD20, 14hp diesel & saildrive Yanmar keyless B-type instrument panel Vetus Sisco single lever throttle Insulated FRP removable engine box

ELECTRICAL

(2) AGM Group 27 90Ah 12V batteries
Yanmar 35A/12V alternator
Blue Sea Systems 360 12V distribution panel
Blue Sea Systems manual battery switch
(2) 12V electrical sockets
Electrical wiring to be ABYC compliant

ELECTRONICS, COMMUNICATION & NAVIGATION

Ritchie X-Port Tactician compass Aquasignal bicolor LED bow light Aquasignal LED stern light Aquasignal LED mast/anchor light

AUXILIARY SYSTEMS

Scandvik stainless steel oval sink Fynspray compact chrome pump faucet Igloo 25 quart marine ice chest 13 gal Plastimo bladder water tank 12 gal RDS aluminum fuel tank 6 gal Vetus polyethylene holding tank with gravity overboard discharge and pump-out capability (3) Stainless steel deck fittings (fuel, water, waste) Jabsco Twist'n'Lock compact manual head Whale Super Sub 650 gph automatic 12V bilge pump mounted in keel sump Whale Urchin manual bulkhead-mounted bilge pump located near helm in cockpit Marelon thru-hull seacocks throughout Plumbing to be ABYC compliant

STEERING & RUDDER

FRP/foam core rudder blade with aluminum rudder stock Jefa twin self-aligning roller bearings in FRP tube Rudder Craft laminated wood tiller

SAFETY EQUIPMENT

Orion Coastal Locator Plus 4 signal kit (4) Kent Type II adult life jackets Cal June Type IV ring buoy & bracket (2) Kidde B-I, 2-5% lb, fire extinguishers West Marine 2.0 medical kit All safety equipment to meet USCG regulations

OUTFIT & FURNISHING

Double-hinged frosted acrylic panels set into bulkhead ring frame

Sunbrella marine upholstery in solid color

3" reticulated foam, box-edge, settee and forward v-berth cushions

Removable main salon settee backrests, padded and upholstered, for dual use as lee boards

White v-groove hull ceiling panels throughout

- Wood fiddles on counters and settee faces
- Wood caps on bulkhead ring frames

Wood handrails on overhead & exterior

Wood sole panel inserts



BLUENOSE YACHT SALES bluenoseyachts@gmail.com 877-695-6538





Wood companionway steps on engine box

Hinged doors on forward bulkhead, outboard of head, and below sink

Sliding mirrored doors outboard of sink

Storage access hatches with integral cubbies on aft bulkhead

- Storage access seat top lift-outs throughout
- (4) Taylorbrite LED reading lights

DECK HARDWARE

- (2) Harken self-tailing radial coachroof winches
- (2) Spinlock XAS triple rope clutches
- (2) Seldén three-sheave deck organizers
- (3) Seldén swivel cam-cleats in cockpit cubbies
- for jib sheet, backstay, and jib furling line
- (2) Harken 8" lock-in winch handles with holders
- Wood flagstaff, ensign, and deck socket
- (4) Stainless steel cockpit sole drains
- (6) Stainless steel 8" cleats and rubstrakes
- (6) Seldén folding stainless steel padeyes
- (1) Seldén fixed stainless steel padeye at bow

WINDOWS, PORTS, & HATCHES

- (6) Flush tempered glass frameless portlights
- (1) Acrylic double-sliding companionway hatch
- (3) Acrylic companionway hatch drop boards
- (2) Cockpit seat flush FRP/foam core hatches
- (1) Lazarette flush FRP/foam core hatch
- (1) Lewmar Low Profile 60 foredeck hatch
- (1) Anchor locker FRP/foam core hatch

ANCHORING, MOORING & OUTFIT

- Wood toe rail mounted over hull-to-deck joint
- 7 lb Fortress aluminum anchor (FX-11)
- 100' x 1/2" diameter nylon anchor rode
- $6' \ge 5/16''$ anchor chain
- (2) Bow & stern lines, 25' nylon, 1/2" diameter
- (2) Spring lines, 35' nylon, 1/2" diameter
- (3) TaylorMade 8" x 20" vinyl fenders
- (1) Floating boat hook

PAINT, COATINGS & FAIRING

Topsides: Evercoat gel coat, Light Grey Deck: Evercoat gel coat, White Non-skid: Evercoat gel coat, Oyster White Boot stripe: Evercoat gel coat, White Cove stripe: Awlgrip, Dark Gray Bilge: Interlux BilgeKote or Evercoat, White

SPARS & RIGGING

Seldén aluminum mast, tapered, deck stepped with compression post below Seldén aluminum boom with single line slab reef system and outhaul Seldén aluminum swept-back spreaders Seldén 1x19 stainless steel wire rigging (3) Stainless steel chainplates Seldén double main halvard/topping lift sheave Seldén double jib halyard sheave Seldén single spinnaker halyard sheave with lead (4) Seldén halvard flip-flop blocks at mast base Seldén MDS mainsail car system Seldén 10:1 below-deck backstay adjusting system Seldén 6:1 gross mainsheet tune Seldén 24:1 fine mainsheet tune Seldén high beam 22mm mainsheet traveler track Seldén 4:1 windward sheeting traveler car system Seldén 30mm self-tacking curved jib track and car Seldén 4:1 jib sheet Seldén Furlex 200TD through deck furler (8) Seldén thru-deck blocks used below deck on bulkheads for jib sheet and furling lines led aft Seldén 4:1 Rodkicker gas spring vang Burgee halyard and block Running rigging package complements hardware

SAILS

Full-batten mainsail w/ single slab reef Furling jib, self-tacking, 90% LP

OPTIONS

Please refer to the Order Form or contact your dealer for a full list of available options

NOTE: Specifications are subject to change at any time due to modifications, substitutions, additions, or deletions at the discretion of Sparkman & Stephens and Bluenose Yacht Sales.



BLUENOSE YACHT SALES bluenoseyachts@gmail.com 877-695-6538

